



GRAYMONT

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: **High Calcium Limestone**
Product Use: Neutralisation, desulphurisation, flux, aggregates, mineral filler, liming, lime, feed ingredient.
Restriction of Use in NZ: Refer to Section 15
New Zealand Supplier: **Graymont NZ**
Address: Hamilton Regional Office
214 Collingwood Street, Level 4
Hamilton, 3204
Telephone: +64 7 839 3210
Toll Free 0800 245 463
Emergency No: 0800 764 766 (National Poison Centre)
Website: www.graymont.com
Date of SDS Preparation: 5 October 2022

Section 2. Hazards Identification

NOT classified as hazardous as per EPA Hazardous Substances (Classification) Notice 2020.

Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Limestone	80 - 100	1317-65-3

Crystalline silica has been found in some products at or above detection level 0.1%. Concentration is dependent upon limestone source. However, using the sedimentation method set out in the draft European Standard followed by XRD analysis, all products were shown to have respirable crystalline silica content of <0.1%.

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention if irritation occurs.

If on Skin: Wash contaminated skin with soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

If Swallowed: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

If Inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.

Product Name: **High Calcium Limestone**
Date of SDS: 5 October 2022

SDS Prepared by: Nexreg Compliance Inc.
Tel: +1-519-488-5126

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion: No known significant effects or critical hazards.

Inhalation: Over exposure: Adverse symptoms may include the following:
respiratory tract irritation, coughing

Skin: No known significant effects or critical hazards.

Eye: No known significant effects or critical hazards.

Notes to Doctor: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Section 5. Fire Fighting Measures

Hazard Type	Non Flammable
Hazards from products	Decomposition products may include the following materials: carbon dioxide metal oxide/oxides At 900°C calcium carbonate decomposes and gives off carbon dioxide and fumes of calcium oxide.
Suitable Extinguishing media	Use an extinguishing agent suitable for the surrounding fire.
Precautions for firefighters and special protective clothing	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
HAZCHEM CODE	None allocated

Section 6. Accidental Release Measures

Personal precautions:

No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions:

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Spill and Disposal procedures:

Small Spill: Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

Large Spill: Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Dispose of waste safely, according to local Council regulations as per Section 13.

Section 7. Handling and Storage

Precautions for Handling:

- Put on appropriate personal protective equipment (see Section 8).

Product Name: **High Calcium Limestone**
Date of SDS: 5 October 2022

SDS Prepared by: Nexreg Compliance Inc.
Tel: +1-519-488-5126

- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
- Workers should wash hands and face before eating, drinking and smoking.
- Remove contaminated clothing and protective equipment before entering eating areas.

Precautions for Storage:

- Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see Section 10) and food and drink.
- Store to minimize dust generation.
- Keep container tightly closed and sealed until ready for use.
- Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
- Do not store in unlabelled containers.
- Use appropriate containment to avoid environmental contamination.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA ppm	mg/m ³	STEL	
			ppm	mg/m ³
Limestone (Calcium carbonate) [1317-65-3]	-	10	-	-

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13TH EDITION.

Engineering Controls

No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Personal Protection Equipment



Eyes	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield.
Hands	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear an

	appropriate NIOSH approved respirator if concentration levels exceed the safe exposure limits.
General	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9 Physical and Chemical Properties

Appearance	Solid (or powder)
Colour	White to grey
Odour	Odourless
Odour Threshold	Not available
pH	8 to 9.2 @ 25°C
Boiling Point	Not available
Melting Point	Not available
Freezing Point	Not available
Flash Point	Not available
Flammability	Not Flammable
Upper and Lower Explosive Limits	Not available
Vapour Pressure	Not available
Vapour Density	Not available
Relative Density	2.68 to 2.76
Density	2.68 to 2.76 g/cm ³
Water Solubility	0.00066g at 20°C
Partition Coefficient:	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	900°C for 760mm pressure
Kinematic Viscosity	Not available
Particle Characteristics	Not available

Section 10. Stability and Reactivity

Stability of Substance	The product is stable.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to Avoid	Do not allow limestone to come into contact with incompatible materials.
Incompatible Materials	Reactive or incompatible with the following materials: oxidising materials and strong acids.
Hazardous Decomposition Products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable. Repeated exposure may cause severe mucous membrane irritation, bronchitis and pneumonia.
Dermal	Not applicable.
Inhalation	Not applicable. Repeated exposure may cause severe mucous membrane irritation, bronchitis and pneumonia. Over exposure may cause respiratory tract irritation and coughing.

Eye	Not applicable.
Skin	Not applicable. Prolonged exposure may cause irritant dermatitis.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Not applicable.
Germ Cell Mutagenicity	Not applicable.
Aspiration	Not applicable.
STOT/SE	Not applicable.
STOT/RE	Not applicable.

Section 12. Ecotoxicological Information

No known significant effects or critical hazards.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available

Section 13. Disposal Considerations

Disposal Method:

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues.

Precautions or methods to avoid: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14 Transport Information

This product is NOT classified as a Dangerous Good for transport in NZ; NZS 5433:2020

Section 15 Regulatory Information

This substance is NOT classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

Section 16 Other Information

Glossary

Cat	Category
EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms

LD ₅₀	inhaling or ingesting it.
LEL	Lethal dose to kill 50% of test animals/organisms.
OSHA	Lower explosive level.
TEL	American Occupational Safety and Health Administration.
TLV	Tolerable Exposure Limit.
	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2020
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document was created by a 3rd party service that has advertised to Nexreg Compliance, Inc. (Nexreg) specialized regulatory knowledge and capabilities in the region(s) where this document is stated to be compliant. We believe the statements, technical information, translations and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. In the event that there is a dispute regarding the document's compliance or content Nexreg will endeavour to provide all reasonable assistance to remedy the problem. It is ultimately the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use. The information herein is given in good faith, but no warranty, express or implied is made.

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand distributor, if further information is required.

Issue Date: 5 October 2022 Review Date: 5 October 2027